

# Umpteen jobs - one machine! Joint and crack cutter FRS 260

**NEW  
2009**

- Cuts wet or dry and flush with the wall regardless of whether the joint is to the left or right of the machine
- Concrete + screed
- Cutting depth up to 90 mm
- Cutting width up to 30 mm when using two cutting discs
- Ammeter for overload check
- Three dust guard models \*)
- Compact pack size

\*) the standard guard for dry cutting is included in the scope of delivery. A guard for wet cutting and a third equipped with a mirror for crack repairs are available on request.

**ALMOST  
DUST  
FREE**

#### Technical data

Voltage: 230 V  
Speed: 6500 rpm  
Power: 2.8 kW  
Cutting depth: 90 mm max.  
Cutting disc: Ø 150 - 260 mm



www.frueh-maschinen.de

Any questions? We've got the answers!

→ +49 7181 92 97 32

**FRÜH**  
maschinen

# Joint and crack cutter FRS 260

The **joint and crack cutter FRS 260** is an ingeniously simple all-rounder of the reliable quality you have come to expect of FRÜH machines.

This extremely versatile machine is operated in an upright position and can be adjusted in height as required. The ammeter monitors the machine's performance and is located in clear view on the guide handle along with the emergency stop button.

1. The cross bar on the guide handle can be moved to the left or right as required. The ammeter and the strain relief for the cable can also be mounted either on the right-hand or left-hand side of the machine.

2. The blade's cutting depth is set using the spindle wheel.

3. The scale on the motor shows the cutting depth. It is also used to set the depth to zero.

4. All protruding parts can be retracted or turned inwards for space-saving transportation.

Scope of delivery: machine complete with ammeter and the standard dust guard

Tech. data are subject to change



This joint cutter has been completely redesigned and can be moved backwards and forwards when in operation. The cutting unit can also be mounted either on the left-hand or right-hand side of the machine.



The control box and the ammeter are located in clear view. Both devices and the cross bar can be mounted either on the left or the right



Pack size of the FRS 260 can be reduced to approx. 68 x 42 x 37 cm for easy transportation in a car



The cutting depth can be set precisely thanks to the spindle wheel used in conjunction with the scale located on the motor.



Erwin Früh GmbH  
Machines and accessories for professional floor treatment and sub-floor preparation

Vorstadtstrasse 61 - 67  
D-73614 Schorndorf  
Fon +49 7181 92 97 32  
Fax +49 7181 92 97 33  
info@frueh-maschinen.de  
www.frueh-maschinen.de



Cuts joints in surfaces to avoid the formation of cracks



Joints are flush with the wall. Only the thickness of the guard - 2 mm - separates any joint from the wall.



Joints measuring up to 15 mm across are possible with one cutting disc



Grooves can be cut using two cutting discs that can be mounted up to 30 mm apart



Chamfer and cutting discs can be mounted together so that joints can be cut and chamfered on one or both sides simultaneously.

# Special accessories for the FRS 260

## Equipment for wet cutting

Comprising a wet dust guard, a piggy-back tank with hose and dosage lever, portable residual current protective device.



Practical: The dosage lever for the water supply is mounted on the cross bar, so that water is supplied as required. Thanks to the difference in height, the water runs out of the tank without the need for external pressure, thus avoiding splashing.



## Equipment for repairing cracks



The dust guard equipped with a mirror is indispensable when widening unwanted cracks for repair. The operator can see the course of the crack and where he must cut to widen it. At the same time the guard offers protection and ensures that any dust that develops is removed immediately.