

FEIN Supercut FSC 2.0

for edge and corner work



Technical data

Voltage:	230 Volts
Power:	400 Watts
Oscillation:	11000 - 18500 1/min
Weight:	approx. 1.3 kg
Cable:	5 m with plug

The **Fein FSC 2.0** is just the thing for work on difficult to access surfaces and perfect for a diverse range of tasks: sanding in tight spaces and corners, removing permanently elastic joints and cutting into surfaces at the edge or close to walls, etc.

This powerful machine works at high speeds in all areas of application. It can be equipped with various diamond, carbide and silicon carbide grinding and cutting tools (see reverse).

Scope of supply: metal tool case, 1 sharpening stone, 1 clamping bolt, 1 wrench.

Tools and accessories FSC 2.0



Carbide coated rasp (triangular)
for the removal of tile adhesive residue,
for sanding down wood and for working
plastics
art. no. 225.014



Diamond sanding triangle
for sanding/grinding corners on mineral
and plastic surfaces etc.
art. no. 225.015 coarse (K 30/35)
art. no. 225.016 fine (K 50/60)



Support base set - Velcro fastener
(2 pieces) for diamond sanding triangle
and paper sanding triangle.
art. no. 125.010



Adapter for carbide coated rasp,
diamond sanding triangle and base
with Velcro fastener.
art. no. 281.645

**Further tools
available on request.**



Diamond triangle, metal bond,
with Velcro fastener for wet and dry
sanding
art. no. 229.111 K 60
art. no. 229.110 K 120
art. no. 229.112 K 200
art. no. 229.113 K 400



Diamond triangle, plastic bond,
with Velcro fastener for wet and dry
polishing
art. no. 229.114 K 500
art. no. 229.116 K 1500
art. no. 229.117 K 3000



Diamond disk, round, 80 mm
for cutting open tile joints and cracks,
for repair cutting, etc.
art. no. 281.061 1.6 mm wide
art. no. 281.060 2.6 mm wide



Cutting blade, straight, for cutting open
and removing elastic joint fillers
art. no. 281.015

Cutting blade, pointed, for cutting
into and removing joint fillers between
building structures
art. no. 281.011



Diamond segment blade for sanding
at corners or obstacles, for cutting
open joints and cracks flush with the
wall, etc.

art. no. 281.016 1.6 mm wide
art. no. 281.017 2.6 mm wide

Diamond blade, straight, for cleaning
and sanding joint edges, etc.
art. no. 281.014



Erwin Früh GmbH
Machines and accessories for professional floor treatment and sub-floor preparation

Vorstadtstrasse 61 - 67, D-73614 Schorndorf
Fon +49 7181 929732, Fax +49 7181 929733

info@frueh-maschinen.de
www.frueh-maschinen.de