

Planing and grinding machine EFS 180 E without chassis



The advantages

- Automatic start interlock to prevent the machine being switched on unintentionally
- Infinitely variable speed control
- Double strain relief, 15 m tear-resistant cable
- Clamp lever for infinitely adjustable guide handle
- Maintenance-free, long-life belt drive

The universal standard machine **EFS 180 E** without a chassis is suitable for planing a whole range of mortar surfaces.

Depending on the tool used this machine is suitable for compacting and planing screeds, for planing epoxy resin mortar and for applying sand or other floor hardeners.

Brushes, milling or grinding discs can also be mounted as required.

ALMOST
DUST
FREE

Any questions?
We've got the answers!

→ +49 7181 92 97 32

Tools and accessories EFS 180 E without chassis



Grinding plate with flexible base for double-sided sand paper and carbide grinding discs



Grinding ring, grit 16: for grinding coarse screed and concrete surfaces



Flat wire steel brush (oil hardened): for cleaning concrete floors and paving stones, for applying primer



Steel planing disc Ø 600 mm: for compacting, planing and levelling screed, concrete, etc.



Plastic planing disc Ø 600 mm for compacting and planing epoxy resin screed and light-coloured mineral screeds



Trowel disc Ø 600 mm with 4 hardened stainless steel planing blades or 48 steel or plastic blades: for skim coats or epoxy screeds



Trowel disc Ø 600 mm with metal or plastic blades for planing anhydride and cementitious screeds and concrete.



Wooden based grinding disc for rubbing poured asphalt



Bladed disc with metal or plastic blades for planing (filling in surface irregularities) magnesite screed

Technical data

Power	1.5 kW
Speed	60 - 180 rpm, infinitely variable
Weight	22.5 kg (without accessories)
Voltage	230 V/50 Hz ac current
Protection	Class I appliance according to VDE

Ø machine	430 mm
Ø tool	400 - 600 mm
Height	gear unit 100 mm motor 220 mm

Scope of delivery

Machine complete with guide handle, 15 m tear-resistant safety cable, start interlock

Subject to technical alterations. Printed in Germany.



Erwin Früh GmbH
Machines and accessories for professional floor treatment and sub-floor preparation

Vorstadtstrasse 61 - 67, D-73614 Schorndorf
Fon +49 7181 92 97 32, Fax +49 7181 92 97 33

info@frueh-maschinen.de
www.frueh-maschinen.de